



File Name: canon sd790 is user manual.pdf

Size: 4666 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 21 May 2019, 20:30 PM

Rating: 4.6/5 from 688 votes.

Status: AVAILABLE

Last checked: 5 Minutes ago!

In order to read or download canon sd790 is user manual ebook, you need to create a FREE account.

[Download Now!](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with canon sd790 is user manual . To get started finding canon sd790 is user manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

canon sd790 is user manual

This page requires Javascript. Modify your browsers settings to allow Javascript to execute. See your browsers documentation for specific instructions. To install your download click on the name of the downloaded file. Access your account, or create a new account, click here to get started. Figures for Movie Mode represent total capacity of the particular media. Canon, DIGIC, ELPH, PIXMA, PowerShot and SELPHY are registered trademarks of Canon Inc. Mac is a trademark of Apple, Inc., registered in the United States and other countries. All other products and brand names are registered trademarks, trademarks or service marks of their respective owners. Recommended Software File Name Date File Size Optional Software File Name Date File Size Recommended Manuals File Name Date File Size Optional Manuals File Name Date File Size The Product purchased with this limited warranty is the only PowerShot Digital Camera to which this limited warranty applies. Warranty exchange or replacement does not extend the original warranty period of the Product. The sole warranty, if any, with the respect to such nonCanon brand items is given by the manufacturer or producer thereof. This limited warranty covers all defects encountered in normal use of the Products, and does not apply in the following cases A Canon Customer Care representative will attempt to diagnose the nature of the problem and correct it over the telephone. If the problem cannot be corrected over the telephone, you will be asked to follow the applicable procedures for MAILIN SERVICE. Note that a dated proof of purchase is required at the time of service. MAILIN SERVICE is a program under which your Product is repaired by a Canon U.S.A. or a Canon Canada authorized service center for the Product. You will be given the name, address and phone number of an authorized service center.

- **canon sd790 is user manual, canon powershot sd790 is instruction manual, canon sd790 is user manual, canon sd790 is user manual free, canon sd790 is user manual download, canon sd790 is user manual software, canon sd790 is user manual online, canon sd790 is user manual 2017, canon sd790 is user manual 2016, canon sd790 is user manual user, canon sd790 is user manual downloads, canon sd790 is user manual.**

It is your responsibility to properly package and send the defective Product, together with a copy of your dated proof of purchase, a complete explanation of the problem and a return address to the authorized service center at your expense. Do not include any other items with the defective Product. The Product covered by this limited warranty and proven to be defective upon inspection will be repaired and returned to you without charge by the authorized service center. Any Product received by the authorized service center that is not covered by the limited warranty will be returned unrepaired, or at the discretion of the authorized service center, you may receive a written estimate of repair at such cost as the service center may establish from time to time. Scroll down to easily select items to add to your shopping cart for a faster, easier checkout. Visit the Canon Online Store Provides uninterrupted power for shooting or downloading. It allows viewing of recorded images from the Canon Powershot Digital Cameras. Effectively doubles the flash range of the camera. Comes with mounting bracket. The cable connects to your camera and to the USB port on your PC or MAC Computer. Comes standard with the EOS 1Ds Mark III, 1D Mark IV, 1D Mark III, 1Ds Mark II, 1D Mark II N, 1D Mark II, 5D Mark II, 7D, 5D, 50D, 40D, 30D, 20D, 10D, Digital Rebel XTi, Digital Rebel XT and Digital Rebel. Please see Compatibility tab for compatible models. Four pieces of weight, plastic pins and weight securing screws are included in the WWDC1 package. Start out by familiarizing yourself with the camera and mastering the basics. Next. Please Read... 6

Getting Started. Please be advised. For CB2LX Remove the battery after charging is complete. Insert the memory card until it clicks into place. Ensure that the memory card is correctly oriented before inserting it in the camera. To Remove the Battery Press the battery lock in the direction of the arrow a and pull the battery out b.

To Remove the Memory Card Use a finger or the toggle on the wrist strap to push the memory card in until you hear a click, then release it. Use the Wrist Strap to Open the Terminal Cover Toggle You can change its position on the strap. Buttons Press the power button. Select the month, day, year and time, and the display order. 1. Use the category. 2. Insert a charged battery into the camera. Or if you use the separately sold AC Adapter Kit ACKDC30, the battery will charge in about four hours. Select a shooting mode. Please note that erased images cannot be recovered. Refer to the Direct Print User Guide for details. Connect the camera to your printer. Print images. You can use the following methods to imprint the date on images lacking imprinted date stamps. Select a shooting mode. 1. Set the mode switch to 2. Turn the control dial to select Standard. Aim the camera at the subject. Do not touch the microphone while recording. Do not press any buttons other than the shutter button. Without changing anything else, press the shutter button all the way press fully to shoot. CameraWindow will display. Macintosh CameraWindow will appear when you establish a connection between the camera and computer. Install the software before downloading images via the Direct Transfer method for the first time p. 26. Buttons Confirm that the Direct Transfer menu is displayed on the camera's LCD monitor. All Images Transfers and saves all images to the computer. Transfers and saves to the computer only the New Images images that have not been previously transferred. The button will blink blue while downloading is in progress. Only JPEG images can be downloaded as wallpaper for a computer. You can produce photo quality prints quickly and easily by connecting them to the camera with a single cable and operating the camera's controls. You can perform the following functions using the control dial. In addition, you can register slideshow or sound recorder functions to the button p. 155.

Power Button Shutter Button Button Turning the Camera Off Shooting Mode Press the power button. Press the Use the menus. A sound file in a format other than WAVE is attached. Overexposure Warning In the following cases, overexposed portions of the image blink. When reviewing an image right after shooting in the LCD monitor Detailed Display When using the Detailed Display mode of the Playback mode Histogram Function The histogram is a graph that allows you to check the brightness of. RedEye Lamp Selftimer AFassist Beam Review Review Info Save Original Auto Category Disp. Overlay Still image Movie IS Mode Still image Movie button. Select Range Select by Date Select by Category Select by Folder Select All Images Clear All Selections Print Setting Page Menu Item. Operation Vol. Selftimer Vol. Shutter Volume Playback Vol. The LCD monitor will not switch to the Detailed Display or Focus Check Display while in the Magnified Display p. 114 or Index Playback mode p. 115. Changing the LCD Monitor Brightness The brightness of the LCD monitor can be changed in the following two ways. The maximum zoom setting before image quality is lost and you can advance the zoom further by pressing the zoom lever toward the icon again. Using the flash in Macro mode may cause image edges to darken. button. button to select button to select. See Memory Cards and Estimated Capacities p. 211. See Image Data Sizes Estimated p. 213. Changing the Compression Still Images Select a compression setting. Use a tripod to shoot. If camera shake is too strong, it may not be fully corrected. If the camera is set at, the ISO speed automatically set by the camera will be displayed when pressing the shutter button halfway or in playback information. Select a shooting mode. 1. Set the mode switch to 2. Allows you to shoot sunsets in vibrant colors. Shoots trees and leaves—such as new growth, autumn leaves or blossoms—in vivid colors.

Shoots without a blue tinge and without making people appear dark against a snowy background. Underwater Appropriate for shooting images with Waterproof Case WPDC24 sold separately. This

mode uses an optimal white balance setting to reduce bluish tones and record images with a natural hue. Actual results may vary according to the subject and shooting conditions. Even if continuous shooting suddenly stops, the memory card may not be full. To Cancel Continuous Shooting Follow Step 1 to display The interval between shots lengthens when the builtin memory of the camera fills. Adjust the zoom before shooting. The zoom factor of the combined optical zoom and digital zoom display on the LCD monitor. When the zoom factor displays in blue, the image will deteriorate. Select the number of recording pixels. 1. Press the 2. Use the and the change the option. You are recommended to use a fully charged battery or an AC adapter since the recording period may be lengthy. The overlapping seams of several adjacent images can be joined into a single panoramic image. Select a shooting direction. Accept the setting. To use the Face Select and Track function, first configure the following settings. The AF lock is convenient because you can let go of the shutter button to compose the image. Press the button and select Aim the camera at the subject on which you wish to lock the exposure. Adjust the exposure compensation to a negative value to avoid making the subject too bright in night shots or when shot against a dark background. Available Shooting Modes Appropriate for standard shooting conditions, including backlit scenes. Select the Long Shutter Mode. 1. Press the 2. Use the 3. Press the Change the shutter speed. 1. Please note that camera shake becomes a factor at low shutter speeds. Shoot with the camera attached to a tripod. Use of the flash may result in an overexposed image. If this occurs, shoot with the flash set to Adjusting the Tone White Balance Normally, the.

Please note that the center frame will not appear when the digital zoom is in use or displays. This can be performed on movies as well as still images, allowing you to enjoy photographing with image or movie effects. However, depending on the shooting conditions, the images may appear rough or you may not get the expected color. Helps Grid Lines confirm the vertical and horizontal positioning of the subject. As the frame does not appear at this point, position the white paper or cloth so it appears in the center of the LCD monitor and then press the function one time, the white balance setting changes to. To Cancel Index Playback Press the zoom lever toward Switching between Sets of Nine Images The jump bar will display if you press the zoom lever toward. Moreover, as you can change the display size and switch images, you can easily check facial expressions and whether a subject's eyes are closed. To Cancel the Focus Check Display Press the MENU button. Jump Shot Date Jump to My Category Jump to Folder Jump to Movie Jump 10 Images. It will resume when you press the button again. Next Frame Last Frame Edit Movies cannot be played in the Index Playback mode. Use the television's controls to adjust the volume when playing a movie on a TV set p. No transition effect. The displayed image darkens and the next image gradually brightens until it is displayed. Press the button to have the previous image display from the left and the button to have the next image display from the right. Image settings for slide shows are based on the Digital Print Order Format DPOF standard. All Images Date My Category Plays the images in the selected category in order. Folder Movies Stills. Up to 998 images can be selected. They will be played back in their order of selection. Select a playback method. Red eyes may not be automatically detected in some images or the results may not turn out as you intended. The uncorrected image is stored.

Although you can apply redeye correction any number of times to an image, the image quality will gradually deteriorate with each application. The following selection of My Colors effects is available. Although My Colors effects can be added any number of times to an image, the image quality will gradually deteriorate with each application and the intended colors may not be achieved. Record Starts recording. Pause Stops recording or playback. The Forward sound cannot be heard while fast forwarding. Select Erases images after selecting them one at a time. For picking a first and last image and erasing all the Select Range images in the range. Select by Date Erases images corresponding to the selected date. Please format the memory card when you want to erase not only image data but also all the data contained on the memory card p. 168. Registering Functions to the You can register a function that you often use to the following functions can be registered. When you

press the camera to Playback mode. When it is pressed again, the registered function is called up. If functions other than cannot be used to turn off the power. Select Range Select by Date Select by Category Select by Folder Select All Images Clear All Selections Only one copy will be printed for each selected image. Images are printed in order according to the file number. A maximum of 998 images can be selected. When the camera is connected to a printer, the will light blue. Order Select single images. Pressing the power button restores camera power. Setting the World Clock When traveling abroad, you can record images with local dates and times simply by switching the time zone setting if you preregister the destination time zones. The time will advance by 1 hour. Select World. 1. Use the button to select 2. Press the Select a destination area. If you change the date and time when the World option is selected, the Home date and time will also change automatically.

You can select how the file number is assigned. A number one higher than the last one recorded is assigned to the next image. Up to 2000 images can be saved into a single folder. New Folder Created Memory Card 1 Continuous. Create New Creates a new folder the next time you shoot images. To Folder create an additional folder, insert the check mark again. You can also specify a date and time if you wish to create Auto Create a new folder using a shooting time after the specified. Turn off the camera and the TV. You can change and register these settings, enabling you to customize the camera to suit your own tastes. Changing My Camera Settings Select a menu item. A computer is required to restore the My Camera settings to the defaults. The builtin rechargeable lithium battery charge is low. LCD monitor Nothing is displayed. The image in the LCD monitor will darken in strong sunlight or bright light. Display flickers. Display flickers when shot under fluorescent lighting. A bar of light purplish red appears on the LCD monitor. Sometimes appears when shooting a bright subject, such as the sun or other light source. Consult the nearest Canon Customer Support Help Desk. Slide the write protect tab upward p. 200. The camera moves when the shutter button is pressed. Subject is out of focal range. The subject is hard to focus Subject in recorded image is too dark. Insufficient light for shooting. Subject is too close, making the flash too strong. The subject is overexposed because the surroundings are too dark. Too much light is shining directly into the camera, or is being reflected off the subject. Continuous shooting slows down. The memory card's performance has dropped. Recording images to memory card takes a long time. Memory card was formatted in another device. The following types of memory cards are used. Slow recording memory cards. Memory cards formatted on a different camera or a computer. Memory cards which have had images recorded and erased repeatedly.

You attempted to play back images shot with another camera or images edited with a computer. File name was changed with a computer or file location was changed. Images cannot be edited. Some images shot with another camera cannot be edited. Movies do not play back correctly. Battery is not being used to its full capacity. Battery will not charge. Battery life exceeded. TV monitor output Image is distorted or not showing on TV monitor. Incorrect video system setting. Memory card full Memory card is full of images and no more can be recorded or saved. In addition, sound cannot be played back. Cannot register this image. You attempted to register an image recorded in a different camera or a movie as a startup image. If this message continues to display, contact your Canon Customer Support Help Desk as there may be a problem with the lens. Do not use organic solvents such as alcohol, benzine, or thinner to clean the equipment. Do not place anything, such as tablecloths, carpets, bedding or cushions, on top of the battery charger while it is charging. Doing so may cause malfunction or damage the LCD monitor. Be careful not to bang the camera or subject it to strong impacts or shocks when wearing or holding it by the strap. Be careful not to bump or strongly push the end of the lens. Be careful not to cover the flash with your fingers or clothing when shooting. The flash may be damaged and emit smoke or noise. The resulting heat buildup could damage the flash. Under these conditions, revive the battery by warming it in a pocket immediately before use. However, ensure that there are no metallic items in the pocket that could cause a short circuit, such as a key ring, etc. Turn the camera power off before connecting or

disconnecting the AC adapter. Use the following procedures to affix the camera and HighPower Flash to the supporting bracket.

To illuminate the subjects properly, install the flash so that it is up against the side of the camera and parallel with the camera's front panel. If dirt remains, contact the closest Canon Customer Support Help Desk as listed on the customer support list supplied with your camera. Subject to change without notice. Exif Print is a standard for enhancing the communication between digital cameras and printers. By connecting to an Exif Printcompliant printer, the camera's image data at the time of. Actual results may vary according to the subject and shooting conditions. Memory card included with the camera. The cable with the ferrite core provided with the digital camera must be used with this equipment in order to comply with Class B limits in Subpart B of Part 15 of the FCC rules. Should the product cease to function in its intended manner, it should be returned to the manufacturer or be discarded. This power unit is intended to be correctly orientated in a vertical or floor mount position. We have 6 Canon PowerShot SD790 IS Digital ELPH manuals available for free PDF download User Manual, Software Manual, Software Users Manual, Product Manual. The stylish Canon PowerShot SD790 IS Digital IXUS 90 IS incorporates a 10 MP CCD sensor and DIGIC III Image Processor delivers sharp images with brilliant color. The 3x 35-105mm optical zoom lens brings faraway objects up close for exceptionally sharp, clear results. The optical image stabilization helps you capture blurfree images in lowlight and when shooting with the zoom. The PowerShot SD790 IS Digital IXUS 90 IS features Face Detection Technology automatically adjust exposure, white balance, flash and focus for superb people shots in all situations. Other highlights include large 3inch LCD screen, Motion Detection, RedEye Correction and Multi Control Dial makes it quick and simple to accessing functions and operations. If something is missing, please contact the retail outlet at which you purchased the product.

This guide is divided into the following two sections. First. p. 7 Getting Started This section explains how to prepare the camera for use and the basics of shooting, viewing and printing images. Start out by familiarizing yourself with the camera and mastering the basics. Next. Learning More p. 37 Once you have mastered the basics, use the camera's many features to shoot more challenging photos. Details on using each function are described in thisPlease note that Canon Inc., its subsidiaries and affiliates, and its distributors are not liable for any consequential damages arising from any malfunction of a camera or accessory, including memory cards, that results in the failure of an image to be recorded or to be recorded in These cards are collectively referred to as memory cards in this guide.Charge IndicatTo Remove the Battery Press the battery lock in the direction of the arrow a and pull the battery out b. To Remove the Memory Card Use a finger or the toggle on the wrist strap to push the memory card in until you hear a click, then release it.Toggle You can change its position on the strap.Or if you use the separately sold AC Adapter Kit ACKDC30, the battery will charge in about four hours. It will charge even if the camera is turned off. Setting the Display LanguExercise adequate caution before erasing an image. You may download and use the Content solely for your personal, noncommercial use and at your own risks. Canon shall not be held liable for any damages whatsoever in connection with the Content, including, without limitation, indirect, consequential, exemplary or incidental damages. You shall also not and shall not let others reproduce, modify, reformat or create derivative works from the Content, in whole or in part. Please try again.Please try again.Then you can start reading Kindle books on your smartphone, tablet, or computer no Kindle device required.

In order to navigate out of this carousel please use your heading shortcut key to navigate to the next or previous heading. Register a free business account If you are a seller for this product, would you like to suggest updates through seller support To calculate the overall star rating and percentage breakdown by star, we don't use a simple average. Instead, our system considers things like how recent a review is and if the reviewer bought the item on Amazon. It also analyzes reviews to verify

trustworthiness. It was released on March 2008. You might not need every tool for every procedure. It is a compact 10.0 megapixel digital camera with builtin flash. It has builtin motion detection and face detection technology. The camera also has a 3.0inch PureColor LCD II screen. A much more in depth background of your product can be found at the Canon Powershot SD790 IS Website. You may find documents other than justWe keep our list of direct Canon PowerShot SD790 IS driver and firmware links uptodate so they are easy to find when you need them.